



G.I. SQUARE HOLLOW POST



FENCE HEIGHT (MM)	PROPOSED SPECIFICATION
1500	50MM X 50MM X 2.3MM X 2000MM
1800	50MM X 50MM X 2.3MM X 2400MM
2100	65MM X 65MM X 2.3MM X 3000MM
2400	65MM X 65MM X 2.3MM X 3000MM
2700	65MM X 65MM X 2.3MM X 3600MM
3000	65MM X 65MM X 2.3MM X 4000MM

G.I. WELDED POST CAP



FENCE HEIGHT (MM)	PROPOSED SPECIFICATION
1500	50MM X 50MM X 3.0MM
1800	50MM X 50MM X 3.0MM
2100	65MM X 65MM X 3.0MM
2400	65MM X 65MM X 3.0MM
2700	65MM X 65MM X 3.0MM
3000	65MM X 65MM X 3.0MM

G.I. FLAT BAR (MS EN 10025 - 2:2011)



FENCE HEIGHT (MM)	PROPOSED SPECIFICATION
1500	50MM X 2.8MM
1800	50MM X 2.8MM
2100	65MM X 6.0MM
2400	65MM X 6.0MM
2700	65MM X 6.0MM
3000	65MM X 6.0MM

G.I. FASTENER SCREW – 8MM x 50MM



FENCE HEIGHT (MM)	PROPOSED QUANTITY
1500	QUANTITY OF FENCE X 10
1800	QUANTITY OF FENCE X 12
2100	QUANTITY OF FENCE X 14
2400	QUANTITY OF FENCE X 16
2700	QUANTITY OF FENCE X 18
3000	QUANTITY OF FENCE X 20

NOTE:

1. The sizes of the post may varies depending on the drawing specification or customer request.
2. G.I. Square Hollow Post and G.I. Flat Bar height tolerance +/- 10mm.